

### **Technical Datasheet**

# **SM-21**

## Special brush solvent

#### **Description**

SM-21 is a specially formulated solvent blend of aliphatic and aromatic hydrocarbons.

#### Fields of application

Specifically designed for thinning PRIMER ACRYL-S acrylic primer. Suitable for thinning varnishes or solvent-based enamel paints to be applied by brush or roller. Also effective for cleaning application tools.

#### **Technical data**

Color: clear / colorless

Density:  $0.77 \pm 0.02 \text{ kg/l}$ 

#### **Directions for use**

Before using SM-21, check the recommended thinning ratio of the product to be used. Then, add the required amount of SM-21 and stir until you get a homogeneous consistency.

#### Consumption

Consumption varies depending on the nature of the application.

#### **Packaging**

0.375 I, 0.75 I & 4 I containers.

#### Shelf life - Storage

36 months from production date, in original, sealed containers, stored at temperatures above 5°C and protected from high temperatures (<+30°C).

#### Remarks

- Ensure adequate ventilation when applying SM-21 indoors.
- Keep away from sources of ignition during application – No smoking.
- Please consult the directions for safe use and precautions written on the packaging before use.
- For further information, please refer to the Material Safety Data Sheet.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:

17th try Theodologiki Ag Athendolog Bood

17<sup>th</sup> km Thessaloniki - Ag. Athanasios Road, P.O. BOX 1043, 570 03 Ag. Athanasios, Greece, Tel.: +30 2310 576 000, Fax: +30 2310 576 029

www.isomat.eu e-mail: support@isomat.eu

